


Muttern · Sonderausführung



Produktklasse A nach DIN ISO 4759 Teil 1

Muttern für V-Nuten 60°
Festigkeitsklasse 10





d	a	Best.-Nr.	a1	e	h	k	⌀
M12	14	506-1214	13,7	22	16	8	60
	16	506-1216	15,7	25	18	9	
M14	16	506-1416	15,7	25	18	9	60
M16	18	506-1618	17,7	28	20	10	60
	20	506-1620	19,7	32	24	12	
M18	20	506-1820	19,7	32	24	12	60
M20	22	506-2022	21,7	35	28	14	60
	24	506-2024	23,7	40	32	16	
M24	28	506-2428	27,7	44	36	18	60

Muttern für V-Nuten 40°
Festigkeitsklasse 10



d	a	Best.-Nr.	a1	e	l	k	⌀
M12	15	500-1215.4	15,4	25	25	15	40
	18	500-1218.4	18,4	29	35		
M16	18	500-1618.4	18,4	29	35	15	40
M20	22	500-2022.4	22,4	35	40	20	40

Muttern für V-Nuten 60°
Festigkeitsklasse 10



d	a	Best.-Nr.	a1	e	l	k	⌀
M12	14	507-1214	14,4	30	25	15	60
M14	16	507-1416	16,4	30	30	15	60
M16	18	507-1618	18,4	40	40	20	60
M20	22	507-2022	22,4	50	40	25	60
M24	28	507-2428	28,4	60	45	30	60